

PICOTE Xpress COATING SYSTEM 2.0

Superior Trenchless Pipe Rehabilitation



The Xpress Brush Coating System provides a revolutionary solution for rehabilitation of 1¼ to 12" (DN32-300) pipes, boasting rapid curing times, zero waste, and quick setup providing unmatched savings in both cost and time.

The Xpress Coating 2.0 Pump features dual hydraulic resin cylinders for the 1:1, 100% solids, single color epoxy. It has a built-in extended life battery and heated resin hoppers with lid locks and heated resin cylinders.

The motorized Delivery Hose Reel has 131' (40m) of delivery hose for easier setup, movement & storage.

USES AND BENEFITS

- **Picote Xpress 1:1 Ratio Epoxy:**
 - As little as 1 hour curing time between coats* (@77°F/25°C).
 - Superior thickness of up to 1mm per layer (@77°F/25°C).
 - Single color (light grey), 100% Solids Epoxy, Zero VOCs.
 - Bucketed resin containers reduce waste & costs.
 - **Resin Heaters** on hoppers and cylinders run off battery to maintain resin temperature during transport & usage.
 - **Motorized Reel with quick connect/multi use hoses:**
 - Hoses are capped & ready for immediate re-use.
 - Eliminates consumables waste and setup time.
 - Almost instantaneous setup for subsequent coats.
 - **Reels:**
 - **Heated Reel** features integrated full length hose heaters. Is needed for Spray Coating.
 - **Standard Reel** includes Reel Heating Blanket, helps maintains hose reel resin temperature. Run off Pump battery or plug in.
 - Vertical design, tri-wheel stair climbers and 32' (10m) corded remote allows easy transport on stairs & hard to reach places.
 - **Go Small!** Includes small diameter hose packages:
 - 1¼-2" (DN32-50) pipes up to 15' (5m) in length.
 - 2-3" (DN50-75) pipes up to 50' (15m) in length.
- *Optional Picote Heater speeds up curing times.

Technical Specifications


Category	Specification
Cylinder Capacity	Pump 2.0: .26 gal (1L) Hopper: 1.4 gal (5.4L)
Weight (empty)	Pump 2.0: 233 lbs (106kg) Std Reel: 110 lbs (50kg) Heated Reel: 140 lbs (64kg)
Size (WxLxH)	Pump 2.0: 26.9x25.7x58.1" (683x653x1476mm) Reels: 23.3x28.8x27.6" (592x734x701mm)
Battery	Internal (24V, 882Wh)
Resin	1:1 / 100% Solids Epoxy

More Info/Guides/Technical Support:

- Visit picoteinstitute.com for e-learning courses, educational videos, quick guides, & manuals.
- For more information on spare parts, assembly and operation, consult the Picote Operation & Safety Manual or contact Picote Technical Support.
- For product training, Picote operates training centers in USA, UK & Finland.

PRODUCTS & PARTS

Product & Parts	
PN	Description
2220300000US	Xpress Coating System 2.0 US Option 1 (Standard Reel)
2220300020US	Xpress Coating System 2.0 US Option 2 (Heated Reel)
2220300000	Xpress Coating System 2.0 Option 1 (Standard Reel)
2220300020	Xpress Coating System 2.0 Option 2 (Heated Reel)
2220300000UK	Xpress Coating System 2.0 UK Option 1 (Standard Reel)
2220300020UK	Xpress Coating System 2.0 UK Option 2 (Heated Reel)
2220300005B	Picote Xpress Epoxy Base (White) US (2.94 gal/30.86 lbs)
2220300005C	Picote Xpress Epoxy Catalyst (Black) US (2.94 gal / 24.15 lbs)
2220300003B	Picote Xpress Epoxy Base (White) EU/UK (14kg/11.13L)
2220300003C	Picote Xpress Epoxy Catalyst (Black) EU/UK (14kg/11.13L)
900004057S	Transparent Delivery Hose for 1-2" (DN32-50) pipes - 16 ft (5m)
900004056S	Transparent Delivery Hose for 2-3" (DN50-75) pipes - 49 ft (15m)
2220300008	Static Mixing Tips & Y-Fitting Package (10pcs)
2220300009	Xpress Static Mixing Tip (10 pcs)
2220300010	Xpress Y-Fitting for Mixing Tip (each)
2220300004	Xpress Reel Heating Blanket (replacement)
<i>Please see the Picote Catalog for the full selection of Coating Brushes and accessories based on your Miller shaft size.</i>	



- Option 1: Xpress Pump 2.0, Standard Hose Reel, Reel Heating Blanket, Small Diameter Hose Packages, and 10 Static Mixing Tips & Y-Fitting Package.
- Option 2: Xpress Pump 2.0, Heated Hose Reel, Small Diameter Hose Packages, and 10 Static Mixing Tips & Y-Fitting Package.

